

Welded Fencing Mesh

Steeledale welded fencing mesh is used in many industry sectors such as agriculture for fencing and enclosures, building and construction for site establishments, meshing and lacing purposes in the mining industry, gabion boxes for retaining walls as well as in the general South African household.



Welded fencing is produced to the highest standards of quality. Thorough testing of wire strength and aperture size is carried out during all stages of manufacturing.

FEATURES

- Intersections are welded to form an integral non-collapsible barrier
- Low maintenance costs
- All wires are either lightly or fully pre-galvanized
- Fencing mesh is ideal for the installation of security alarm systems

APPLICATION

- Industrial perimeter security
- Domestic perimeter security
- Schools
- Prisons
- Freeway partitioning
- Racking enclosure



The mesh is produced from 1.6mm ø to 4.0mm ø lightly and heavy galvanized wire in accordance with SANS 675:2011.

APERTURES (mm)	HEIGHT (m)	WIRE DIAMETER (mm)
50 x 25	1.22	2.0 / 2.5 / 3.15 / 4.0
	1.83	
	2.42 / 2.72	
50 x 50	1.22	2.0 / 2.5 / 3.15 / 4.0
	1.83	
	2.42 / 2.72	
75 x 75	1.22	2.0 / 2.5 / 3.15 / 4.0
	1.83	
	2.42 / 2.72	
100 x 50	1.22	2.0 / 2.5 / 3.15 / 4.0
	1.83	
	2.42 / 2.72	
100 x 75	1.22	2.0 / 2.5 / 3.15 / 4.0
	1.83	
	2.42	
100 x 100	1.22	2.0 / 2.5 / 3.15 / 4.0
	1.83	
	2.42 / 2.72	

APERTURES (mm)	HEIGHT (m)	WIRE DIAMETER (mm)
25 x 13	0.910	
	1.220	1.6 / 2.0
	1.830	
25 x 25	0.910	
	1.220	1.6 / 2.0
	1.830	
50 x 13	0.910	
	1.220	1.6 / 2.0
	1.830	
50 x 25	0.910	
	1.220	1.6 / 2.0
	1.830	
50 x 50	0.910	
	1.220	1.6 / 2.0
	1.830	
100 x 50	0.910	
	1.220	1.6 / 2.0
	1.830	
100 x 100	0.910	
	1.220	1.6 / 2.0
	1.830	